



An ISO 9001:2008 Co.



measurably fresh



[www.airefengineers.net](http://www.airefengineers.net)



## TREATED FRESH AIR UNITS

Double skin | Floor mounted | Belt driven



Choose your air.

# TREATED FRESH AIR UNITS

Double skin | Floor mounted | Belt driven




## GENERAL DESCRIPTION

The treated fresh air units are equipped with the latest of components and fittings that impart smooth working and easy maintenance capabilities to them. The flexibly designed units are available in double skin casings fitted with statically and dynamically balanced, AMCA certified centrifugal blowers, high quality filters and high efficiency cooling / heating coils of various capacities.

**RANGE :** 1000 CFM to 6000 CFM (Higher capacities are available as well)

## CONSTRUCTIONAL FEATURES

FRAME	:	Extruded Aluminum profile and 3D nylon corners etc.
BASE	:	Heavy gauge GSS base frame with cast Al corners
CASING	:	23 ± 2 mm thick, double skin panels made of 0.6 mm sheets with Poly Urethane Foam (PUF) of density 38 ± 2 kg/cu.m injected between the two skins
COOLING COILS	:	DX/CW type made up of Copper pipe and Aluminum fins, duly tested at 350 lbs under water, 6 rows deep
FILTERS	:	Synthetic, cleanable pre filters
BLOWERS	:	AMCA certified DIDW type, centrifugal blowers Common-rail base for blower-motor assembly on vibration isolation pads
MOTORS	:	TEFC type, Three phase motors of standard make
MOTOR STAND	:	Adjustable motor-mounting fixture
PULLEYS	:	Adjustable Taper-Bush type pulleys
DRAIN PAN	:	Dual GSS pan with sandwiched insulation and inherent slope
CANVAS CONNECTION	:	Flexible connection to isolate blower from unit body



## CHARACTERISTICS

MODULAR CONSTRUCTION	:	For easier maintenance of the units
DOUBLE SKIN CASING	:	Higher efficiency and low noise
VIBRATION ISOLATORS	:	The units are provided with blower-motor assembly mounted on vibration isolators to make the units vibration free.
PORTHOLE	:	Viewing glass is provided for easier inspection without opening the door
GASKET SEALED PANELS	:	Low leakage and quiet operation is ensured by using high quality gasket to seal the panels, doors etc.
ADJUSTABLE MOTOR STAND	:	The belt tension can be easily adjusted by screwing or unscrewing the bolt provided on the motor stand
FLEXIBLE CONNECTION	:	High quality canvas connections prevent vibrations to be carried over from the blower to the unit body

**APPLICATIONS :** Hotels, Restaurants, Offices, Shops, Auditoriums, Hospitals, Banquet Halls, Banks, Apartments etc.

**OPTIONAL :** S.S. Drain Pan, Eliminator / Humidifier / Dehumidifier sections, Limit Switch, Volume Control Dampers



Choose your air.

## Airef Engineers

570, Industrial Area, Phase - 9, Mohali - 160062, Punjab, India  
**T:** 0172 2232580 **M:** 9814178328, 9872924004, 9814636328  
**e mail:** mail@airefengineers.net **Website:** www.airefengineers.net